

EPOXY & FIBERGLASS FLOORING, SEAMLESS FIBERGLASS WALL SYSTEMS, SEALERS, HIGH PERFORMANCE COATING SYSTEMS, AND INDUSTRIAL CLEANERS

PRODUCT BULLETIN PR-203 COLD STRIP

DESCRIPTION

PR-203 IS A FREE FLOWING, INDUSTRIAL STRENGTH, ACTIVATED, METHELENE CHLORIDE TYPE, PAINT REMOVER. IT IS NON-FLAMMABLE AND NON-CORROSIVE.

USES

PR-203 IS PARTICULARLY USEFUL FOR REMOVAL OF TOUGH ENAMELS AND EPOXY COATINGS, AND FOR USE WHERE PASTE TYPE PAINT REMOVERS WOULD BE DIFFICULT TO USE. PR-203 WORKS WELL AS A SOAK TANK STRIPPER FOR PAINT REMOVAL ON PARTS AND EQUIPMENT. IT IS A GENERAL PURPOSE HORIZONTAL SURFACE PAINT REMOVER AND IT IS VERY USEFUL IN REMOVING FLOOR COATINGS.

APPLICATION

SPRAY OR POUR PR-203 ONTO THE SURFACE TO BE STRIPPED OR IMMERSE THE PART IN IT. IN A FEW MINUTES THE COATING WILL BLISTER AND BUCKLE ALLOWING THE COATING TO BE SCRAPED OR RINSED OFF EASILY. FOR MULTIPLE COATS, A FEW QUICK SCRATCHES ACROSS THE SURFACE WILL ALLOW PR-203 TO PENETRATE UNDER THE COATING AND REMOVE IT. ALWAYS WARM THE PRODUCTS TO ROOM TEMPERATURE BEFORE USE. DO NOT USE ON HOT SURFACES SINCE FLAMMABLE VAPORS MAY RESULT.

CAUTION

PR-203 CONTAINS VOLATILE SOLVENTS, INCLUDING METHELENE CHLORIDE. USE WITH ADEQUATE VENTILATION AND EXTINGUISH ALL OPEN FLAMES IN THE WORK AREA. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS AND PROLONGED SKIN CONTACT. USE CAUTION, WEAR RUBBER GLOVES, BOOTS, APRONS AND EYE PROTECTION. IN CASE OF SKIN CONTACT, FLUSH WITH WATER. IN CASE OF EYE CONTACT, FLUSH WITH WATER FOR AT LEAST 15 MINUTES AND SEEK IMMEDIATE MEDICAL ATTENTION. IF TAKEN INTERNALLY, DO NOT INDUCE VOMITING, DILUTE WITH LARGE VOLUMES OF WATER OR MILK OF MAGNESIA AND GET IMMEDIATE MEDICAL ATTENTION. FREEZING MAY CAUSE PRODUCT TO SEPARATE. REWARM AND STIR BEFORE USE.

NOTE

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, C.D. PRODUCTS, INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.