



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-6685
or 1-800-221-6381

Fax: 920-739-8704
EMAIL: CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

FLORIDYNE™ TOP BLOCKER

WATER, OIL AND STAIN RESISTANT CONCRETE SEALER

IDEAL FOR GARAGES, DRIVEWAYS, RUNWAYS, WAREHOUSES, PARKING RAMP, MACHINE SHOPS, INDOORS OR OUTDOORS

DESCRIPTION

FLORIDYNE™ TOP BLOCKER IS A SPECIALLY FORMULATED, HIGHLY DURABLE PENETRATING SEALER THAT REACTS WITH THE SILICA IN THE CONCRETE SURFACE, HARDENS AND DENSIFIES CONCRETE. FLORIDYNE™ TOP BLOCKER MAKES MOST CONCRETE SURFACES TOTALLY IMPERVIOUS TO OIL AND OTHER STAINING AGENTS, ALTHOUGH A ROUGH CONCRETE SURFACE MIGHT ALLOW SPILLS TO MIGRATE INTO THE ROUGH AREAS MAKING CLEANING DIFFICULT. THE RESULTING SEALED SURFACE WILL NOT ALLOW PAINTS TO SUCCESSFULLY ADHERE TO IT.

USES

FLORIDYNE™ TOP BLOCKER IS ESPECIALLY USEFUL ON NEW CONCRETE OR THAT HAS BEEN TREATED WITH A SILICATE OR SILICANATE DENSIFIER (RESPECTIVELY ASHFORD FORMULA OR EUCLID DIAMOND HARD FOR EXAMPLE). SUCH MATERIALS "FILL" THE SURFACE BUT USUALLY STAIN IF OIL OR OTHER AGENTS ARE SPILLED. FLORIDYNE™ TOP BLOCIER COMPLETELY ELIMINATES SUCH STAINING AND FINISHES THE JOB OF "SEALING OFF" THE TOP OF THE CONCRETE. FLORIDYNE™ TOP BLOCKER, SOLELY, MAY BE USED OVER POLISHED CONCRETE, EXPOSED AGGREGATE AND CLAY TILES FOR THE SAME EFFECT

APPLICATION

APPLY FLORIDYNE™ TOP BLOCKER AT A RATE OF 750 SQFT PER GALLON PER COAT . FOR VERTICAL SURFFACES A GREATER COVERASGE RTE IS SUGGTESTED TO KEEP THE PRODUCT FROM RUNNING. **THE NUMBER OF COATS NEEDED IS VERY DEPENDENT ON THE CONCRETE PORIOUSITY.** YOU MAY USE A PUMP UP SPRAYER OR A ROLLER. FLORIDYNE™ TOP BLOCKER IS A VERY THIN PRODUCT SO APPLYING TWO OR THREE COATS ON IN SUCCESSIVE THIN LAYERS IS OFTEN A MORE EVEN APPLICATION ESPECIALLY IF ROLLED. FLORIDYNE™ TOP BLOCKER IS VERY CONCRETE SPECIFIC AND TIGHT CONCRETE WILL ACCEPT LESS MATERIAL THAN MORE OPENLY TROWELED CONCRETE. WAITING 12 HOURS OR MORE BETWEEN COATS IS A GOOD IDEA SO EACH COAT CAN PENETRATE TO AS GREAT AN EXTENT AS POSSIBLE. THE FINAL PROPERTIES ARE DEVELOPED AFTER 2 DAYS AT 65F OR ABOVE. UNREACTED FLORIDYNE™ TOP BLOCKER MAY BE EASILY REMOVED WITH CD-103.

RESISTANCES -24 HR OR TO DRYNESS

| | | | | | |
|-----------|---|---------|----------|--------|------------|
| MOTOR OIL | NO STAIN | MUSTARD | NO STAIN | LEMON | DOES STAIN |
| KETCHUP | NO STAIN | COFFEE | NO STAIN | GREASE | NO STAIN |
| TRACTION | FLORIDYNE TOP BLOCKER IS 12% LESS SLIPPERY THAN EUCLID DIMAOND HARD | | | | |

CAUTION

KEEP OUT OF REACH OF CHILDREN. IF SPLASHED IN EYES RINSE FOR 15 MINUTES AND SEEK MEDICAL ATTENTION. THIS PRODUCT HAS LOW ODOR BUT IS COMBUSTIBLE SO KEEP AWAY FROM OPEN FLAMES AND IGNITION SOURCES.

NOTE

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, C.D. PRODUCTS, INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.