



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
or 1-800-221-6381
Fax: 920-739-8704
EMAIL: CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

#2101-40 and 64 POLYURETHANE FLOOR SEALER

DESCRIPTION: #2101 POLYURETHANE FLOOR SEALER is a water clear, one package, aromatic moisture cure urethane coating. It quickly cures to a tough, hard film, with outstanding abrasion resistance, good chemical resistance and good flexibility. Available in 40% solids and 64% solids versions.

USES: #2101 provides an excellent, easy to apply general purpose, industrial and commercial concrete floor coating. It is recommended for gymnasium floors or other heavy duty wood coating requirements such as masonry forms, hopper and box car lining and wood floors.

APPLICATION: For best results #2101 should be applied over a cleaned concrete surface primed with a suitable penetrating primer such as #1020 PENETRATING EPOXY, or #2100 PENETRATING URETHANE. It should be applied in thin, even coats at not more than 300 sqft./gal, as soon as each coat is cured enough to walk upon but within 24 hours of that coat drying. Application may be by roller, brush or spray. Tack free time is 2-4 hours, depending on temperature and humidity, with full use allowable 24 hours after application. Thinning may be up to 5% with Xylene. Clean up with Xylene. Keep containers tightly closed when not in use.

SPECIFICATIONS:

SOLIDS -	40% or 64%	GARDNER COLOR 1-	2
TACK FREE -	3 HR -5HR	SWORD HARDNESS -	23
LIMITED USE -	12 HR	PENCIL HARDNESS -	2H
FULL USE -	24 HR	GLOSS -	EXCELLENT
TABOR ABRASION -	10	SOLVENT RESISTANCE -	GOOD

CAUTION: Contains flammable solvents. Extinguish flames and eliminate ignition sources during application. #2101 contains a trace % of free isocyanate monomer so refer to msds sheets for safe handling and application information.

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.