



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685 OR
1-800-221-6381
Fax: 920-739-8704
EMAIL: CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

#990/#991 TOP CHOICE SEALER

DESCRIPTION: #990 TOP CHOICE (or the higher solids version: 991 TOP CHOICE) is a single component, low viscosity resin solution designed for application by pump or airless spray, roller or brush. It is available in clear only.

USES: #990 TOP CHOICE is ideally suited for concrete applications. It may be applied over fresh concrete to entrap moisture so the concrete cures fully. It may also be easily applied over itself at a later time do provide a high gloss floor surface finish. #990 TOP CHOICE is an economical floor surface that wears well and gives good protection against a variety of chemical splash conditions.

APPLICATION:

1. As a concrete cure and seal material: apply #990 sealer as soon as the concrete has cured sufficiently to allow workman to walk across it without leaving foot prints and all bleed water has dried. Using a pump type sprayer, apply #990 sealer at a rate of 300-500 sqft/ gal evenly to the top surface.
2. As a top sealer: thoroughly clean the surface with a mild industrial cleaner like cd-203 pronto diluted 10:1 with water. Rinse all residue off surface and allow to dry. Extinguish all flames , pilot lights and eliminate any other ignition sources in the area. Recoat with a roller or spray at a rate of 250-350 sqft/gal. Dry time is approximately 2 hours. For additional shine apply a second top coat.

SPECIFICATIONS:

Solids 990:	20%
Solids 991	26%
Flammability:	Flammable Liquid- Red Label
Hardness:	2H
Gloss:	Excellent
Clarity:	Gardner 1 Color, Excellent Gloss And Shine
Good Splash Resistance:	NaOH, KOH, Motor Oil, Dilute H ₂ SO ₄ , HCl and Acetic Acid
Not Recommended:	Solvents, Concentrated Acids, Long Term Chemical Exposure

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.