



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
OR 1-800-221-6381
Fax: 920-739-8704

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN CD-320 AROMATIC E

DESCRIPTION

CD-320 IS A CLEAR BLEND OF HIGH BOILING POINT AROMATIC SOLVENTS. ITS EMULSIFIERS ALLOW CD-320 AND THE CLEANING RESIDUES TO BE QUICKLY WASHED AWAY WITH WATER.

USES

CD-320 HAS THE SOLVATING POWER OF XYLOL WITHOUT THE FLAMMABILITY. IT WORKS WELL AS A GENERAL PURPOSE DEGREASER AND PARTS CLEANER. IT WAS ORIGINALLY DEVELOPED TO REMOVE STYRENE AND CHLORINATED RUBBER SEALERS FROM CONCRETE SAFELY. IT MAY BE SPREAD OVER A LARGE AREA, SCRUBBED AND RINSED AWAY WITH MINIMAL CHANCE OF FIRE OR IGNITION. IT EMULSIFIES QUICKLY WITH WATER FOR FAST RINSING.

APPLICATION

APPLY CD-320 TO THE SURFACE TO BE CLEANED AND LET SIT A FEW MINUTES. TO REMOVE CONCRETE CURING COMPOUNDS, SCRUB THE SURFACE WITH A FLOOR MACHINE EQUIPPED WITH A STIFF BRUSH. FLUSH THE SURFACE WITH WATER TO REMOVE THE DISSOLVED MATERIAL. UNDER CURRENT ENVIRONMENTAL REGULATIONS, IF AN EFFLUENT CONTAINS LESS THAN 10% SOLVENT IT IS NOT CONSIDERED A HAZARDOUS WASTE.

CAUTION

CD-320 IS NOT FLAMMABLE OR COMBUSTIBLE UNDER CURRENT DEFINITIONS, BUT CARE SHOULD BE TAKEN TO EXTINGUISH ALL FLAMES OR IGNITION SOURCES IN THE AREA. DO NOT USE TO CLEAN HOT ENGINES OR PARTS SINCE HOT VAPORS MAY BURN. IF TAKEN INTERNALLY, DO NOT INDUCE VOMITING AND SEEK IMMEDIATE MEDICAL ATTENTION.

NOTE

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, C.D. PRODUCTS, INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.