



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
or 1-800-221-6381
Fax: 920-739-8704
EMAIL: CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

EPOXY BOOSTER

DESCRIPTION

EPOXY BOOSTER is a multi functional polyamine material which may be added to many epoxy/amine blends to speed the reaction.

USES

EPOXY BOOSTER is useful in shortening cure times and allowing a material to react at slightly lower temperatures than would normally be expected

APPLICATION

Thoroughly mix the epoxy material first. Add epoxy booster in quantities of 1-2% by volume of the mixed material again mixing all materials thoroughly. A 2%, by volume, addition of EPOXY BOOSTER will shorten cure time in a high or 100% solids material by approximately 25%. Pot life will also be similarly shortened and the exothermic heat developed in the reaction will likely increase. Use of EPOXY BOOSTER in excess of these levels will add an increasingly yellow tint to the materials and likely alter the epoxy ratios and change the finished film qualities. For these reasons we do not recommend a greater addition than 2%.

CAUTION

EPOXY BOOSTER is strongly alkaline. Casual contact can cause burns to sensitive skin areas especially eyes.

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.