



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
or 1-800-221-6381
Fax:920-739-8704
EMAIL:CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

FISH-EYE KILLER

DESCRIPTION

FISH-EYE KILLER is a silicone type additive which lowers the surface tension of most epoxy and urethane materials. A lower surface tension frequently improves adhesion of the product to the substrate and allows the material to spread more readily and so diminish or eliminate fish-eyes.

USES

FISH –EYE KILLER may be added to most high or 100% solids epoxies and solvent born epoxy or urethane coatings. It should not be added to water based materials.

APPLICATION

Add FISH-EYE KILLER to the mixed material after it has been determined that the material flow and substrate wetting is insufficient. FISH-EYE KILLER may be added up to 0.1% by volume of the material though amounts in the 0.01-0.05 range are normally sufficient. These amounts may be estimated on the job with 40 grams (approximately 0.13 fluid ounce) being approximately 0.1% of a gallon.

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.