



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
or 1-800-221-6381
Fax: 920-739-8704
EMAIL: CDPEPOXY@AOL.COM

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

FLORIDYNE™ SYSTEM

WATER, OIL AND STAIN RESISTANT CONCRETE SEALER

**IDEAL FOR GARAGES, DRIVEWAYS, RUNWAYS, WAREHOUSES, PARKING RAMPS,
MACHINE SHOPS, INDOORS OR OUTDOORS**

DESCRIPTION

THE FLORIDYNE™ SYSTEM IS A SPECIALLY FORMULATED, HIGHLY DURABLE PENETRATING SEALER SYSTEM THAT REACTS WITH THE SILICA IN THE CONCRETE SURFACE, HARDENS AND DENSIFIES CONCRETE. FLORIDYNE™ MAKES MOST CONCRETE SURFACES TOTALLY IMPERVIOUS TO OIL AND OTHER STAINING AGENTS. THE SYSTEM USES FLOIRDYNE™ FOR GENERAL PURPOSE APPLICATIONS AND FLORIDYNE™ TOP BLOCKER FOR HIGH OIL AND GREASE EXPOSURE AREAS. FLORIDYNE™ MAY BE RECOATED WITH ITSELF IN THE FUTURE, THE RESULTING SEALED SURFACE WILL NOT ALLOW PAINTS, OTHER THAN OUR EPOXIDYNE SYSTEM, TO SUCCESSFULLY ADHERE TO IT.

USES

FLORIDYNE™ IS ESPECIALLY USEFUL ON NEW CONCRETE THAT HAS BEEN TREATED WITH A SILICATE OR SILICANATE DENSIFIER (RESPECTIVELY ASHFORD FORMULA OR EUCLID DIAMOND HARD FOR EXAMPLE). SUCH MATERIALS "FILL" THE SURFACE BUT USUALLY STAIN IF OIL OR OTHER AGENTS ARE SPILLED. FLORIDYNE™ COMPLETELY ELIMINATES SUCH STAINING AND FINISHES THE JOB OF "SEALING OFF" THE TOP OF THE CONCRETE. FLORIDYNE™ AND FLORIDYNE™ TOP BLOCKER SOLELY, MAY BE USED OVER POLISHED CONCRETE AND CLAY TILES FOR THE SAME EFFECT.

APPLICATION

UNSEALED CONCRETE. REQUIRES TWO COATS OF FLOIRDYNE™ EACH AT 300- 350 SQFT/GAL. YOU MAY USE A PUMP UP SPRAYER OR A ROLLER. FLORIDYNE™ IS A VERY THIN PRODUCT SO APPLYING SUCCESSIVE THIN LAYERS IS MORE EFFECTIVE THAN HEAVY LAYERS. OVER ALREADY DENSIFIED CONCRETE APPLY ONE COAT OF FLORIDYNE™ OR FLORIDYNE™ TOP BLOCKER AT 500-800 SQDFT PER GAL. TIGHT CONCRETE WILL ACCEPT LESS MATERIAL THAN MORE OPENLY TROWELED CONCRETE. WAITING 12 HOURS OR MORE BETWEEN COATS IS A GOOD IDEA SO EACH COAT CAN PENETRATE TO AS GREAT AN EXTENT AS POSSIBLE. THE FINAL PROPERTIES ARE DEVELOPED AFTER 7 DAYS AT 65F +.

RESISTANCES -24 HR OR TO DRYNESS

MOTOR OIL	NO STAIN	MUSTARD	NO STAIN	LEMON	DOES STAIN
KETCHUP	NO STAIN	COFFEE	NO STAIN	GREASE	NO STAIN

CAUTION

KEEP OUT OF REACH OF CHILDREN. IF SPLASHED IN EYES RINSE FOR 15 MINUTES AND SEEK MEDICAL ATTENTION. THIS PRODUCT HAS LOW ODOR BUT IS COMBUSTIBLE SO KEEP AWAY FROM OPEN FLAMES AND IGNITION SOURCES.

NOTE

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, C.D. PRODUCTS, INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.

PACKAGING

4 X 1 GAL CONTAINERS
5 GAL PAILS
55 GAL DRUMS