



PRODUCTS, INC.

918 N. Union Street
Appleton, WI 54911
920-739-8685
or 1-800-221-6381

Epoxy & fiberglass flooring, seamless fiberglass wall systems, sealers, high performance coating systems, and industrial cleaners

PRODUCT BULLETIN

PFAC

DESCRIPTION

PFAC – POLYUREA FILLER AND CAULK is a two component polyurea/amine blend that provides a hard, tough surface. **PFAC** may be used as a stand alone spall or hole filler, as an all purpose crack and joint filler or mixed with various aggregates to provide a build up or slip resistant surface. **PFAC** is in-line blended utilizing a two component mixer/sprayer apparatus or a hand held plural component caulk gun allowing the applicator to use amounts ranging from a few ounces to nearly continuous feed. **PFAC IS AVAILABLE IN BLACK, GRAY, AND SANDSTONE (near concrete color).**

USES

PFAC may be supplied in a two component “caulk gun” system for minor repairs, holes and crack filling or professionally installed with high pressure two component mixing apparatus. **PFAC** exhibits excellent adhesion to wood, tiles, concrete, asphalt, glass, brick, shingles, metals or other clean surfaces. **PFAC NEEDS NO PRIMER**, has excellent weather and water resistance, may be used indoors or outside, and **CURES TO –20F**. It has good thermal resistance to 300F and excellent thermal cycling resistance. **PFAC** is a good choice as a weather resistant concrete crack and joint filler, roof patch, truck bed patch, rail road car patch, wood dry kiln patch, equipment seam repair and patch material. **PFAC** is especially useful in areas that are continually wet.

APPLICATION

Clean and properly prepare surface. Steel should be sand blasted, concrete should be chemically cleaned or mechanically abraded, wood should be sealed against moisture migration. Floor cracks and holes should be thoroughly cleaned with an acid detergent – XA-201 is a good choice – and/or a good degreaser – CD-103 is a good choice or mechanically abraded. Consult us for chemical resistance recommendations.

SPECIFICATIONS

SOLIDS – 100%

WATER RESISTANCE- EXCELLENT

FLEXIBILITY – 400%

SET TIME –1 MIN

ADHESION: + 350PSI (concrete fails)

CHEMICAL RESISTANCE- EXCELLENT

DUROMETER 65

UV RESISTANCE- EXCELLENT

HEAT RESISTANCE – TO 300F

ODOR – NONE

FLASH POINT: +200F

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.