

MATERIAL SAFETY DATA SHEET

C.D. PRODUCTS, INC. emergency telephone #
918 N. Union St.. (920)-739-8685
Appleton, WI 54911 ISSUE DATE- 05/11/2000

SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME- PART B HARDENER

PRODUCT #- 3100B

PRODUCT CLASS- ALIPHATIC AMINE

HMIS CODE HEALTH-1 , FIRE-1, REACTIVITY-0

HAZARD RATING: 0=LEAST, 1=SLIGHT, 2= MODERATE, 3=HIGH, 4= EXTREME

SECTION II: HAZARDOUS INGREDIENTS	CAS	%	PEL	TLV
benzine-1, 3dimethanmine	1477-55-0	<10	na	na(1)
trimethylhexamethylenenedimamine	3236-53-1	>10	na	na
paratertiarybutylphenol	98-54-4	<10	na	na
nonyl phenol	25154-52-3	<10	na	na
n-aminoethyl piperazine	140-31-8	>20	na	na

(1)Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption.

SECTION III: PHYSICAL DATA

BOILING RANGE: > 400F

EVAPORATION RATE VS BUTYL ACETATE -na

VAPOR DENSITY VS AIR: na

SOLUBILITY IN WATER: not soluble

APPEARANCE AND ODOR: clear viscous liquid

PERCENT VOLATILE BY VOLUME: 0

WEIGHT PER GALLON: 8.0b/gal

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): +200F

LEL: 0.8 estm

UEL: na

EXTINGUISHING MEDIA: water spray, dry chemical, foam or carbon dioxide

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide, carbon monoxide, oxides of nitrogen

SPECIAL FIRE FIGHTING PROCEDURES: water spray to keep containers cool, and to protect persons attempting to stop leaks. Wear goggles and full protective clothing. Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter, especially is sprayed into containers of hot material.

SECTION V: HEALTH HAZARD DATA - EFFECTS OF OVER EXPOSURE

INGESTION: can cause gastrointestinal irritation, nausea, vomiting, diarrhea

INHALATION: excessive inhalation of vapors can cause nasal and respiratory irritation

SKIN ABSORPTION: may cause burns and or sensitization

SKIN CONTACT: above

EYE CONTACT: causes chemical burns and may cause irreversable injury

EFFECTS OF CHRONIC OVER EXPOSURE: NA

EMERGENCY FIRST AID PROCEDURES

EYE CONTACT: flush with water for 15 minutes, lifting upper and lower lids, and seek medical attention

SKIN CONTACT: wash immediately with soap and water, remove contaminated clothing and launder before reuse.

INGESTION: do not induce vomiting, keep person warm and quiet and seek medical attention. Aspiration of ingested material into the lungs can cause chemical pneumonias which can be fatal.

INHALATION: remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped administer artificial respiration. Keep person warm and quiet and seek medical attention.

SECTION VI: REACTIVITY DATA

STABILITY: stable

HAZARDOUS POLYMERIZATION: will not occure

CONDITIONS TO AVOIDS excessive heat, contact with strong acids

SECTION VII: SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: eliminate ignition sources, absorb with inert material, eg- sand, scoop up and put into disposal container. flush area with water, prevent washdowns from entering the sewers and water ways. Uncontrolled spills which exceed one gallon may be reportable to the National Response Center. For small spills the resin may be scooped us and then disposed of.

WASTE DISPOSAL METHOD: dispose of in accordance with applicable local, state, and federal regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY: use with adequate ventilation. NIOSH/MSA approved respirators

should be used where ventilation is not adequate. Niosh approved air-line respirators with auxiliary escape air tanks or self contained breathing apparatus should be used in confined spaces.

VENTILATION: local exhaust recommended when appropriate to control employee exposure below TLV limits

PROTECTIVE GLOVES: Neoprene, nitrile rubber -should be warn

EYE PROTECTION: chemical splash goggles

OTHER PROTECTIVE EQUIPMENT: normal work clothing covering arms and legs to prevent skin contact.

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: keep containers tightly closed.

OTHER PRECAUTIONS: keep away from heat or open flames

SECTION X: ADDITIONAL R-T-K COMPOSITION INFORMATION

no additional informatino is applicable

MSDS SHEET C.D. PRODUCTS INC. #3100 PART B HARDINER PAGE 3

SECTION XI: SARA TITLE III INFORMATION

Supplier is notified under SARA TITLE III SECTION 313 not required for this product. SARA SECTION 311 and 312 hazard classification for this product is listed below

Immediate (acute) health hazard

Delayed (chronic) health hazard

SECTION XII: RCRA INFORMATION

Since this product is not sold as a waste, we have not listed it as a waste. Based on our knowledge of this product, its raw materials and processes employed during its manufacture, we believe it is unlikely that this product is a hazardous waste for federal RCRS purposes. We recommend that you carry out your own tests and evaluations prior to discarding any materials.

SECTION XIII: CERCLA INFORMATION

Under EPA-CERCLA releases to air, land or water which exceed the reportable quantity must be reported to the national response center (800-424-8802). This product contains no materials with reportable quantities.

SECTION XIV: CALIFORNIA PROPOSITION 65 INFORMATION

This product is not subject to California Proposition 65 notification.

SECTION XV: TRANSPORTATION INFORMATION

Dot shipping name: alkylamines n.o.s

Dot hazard class: corrosive

Dot label(s): corrosive

Dot UN/NA number: UN 2735

SECTION XVI: OTHER INFORMATION

This product complies with all TSCA inventory requirements.

NOTE: To the best of our knowledge, the information contained herein is accurate. However C.D. Products. Inc assumes no liability whatsoever for the accuracy or completeness of the information contained herein. The final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.