

# MATERIAL SAFETY DATA SHEET

C.D. PRODUCTS, INC.                      emergency telephone #  
918 N. Union St..                      (920)-739-8685  
Appleton, WI 54911                      ISSUE DATE- 3/1/90

## SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME- EPOXY RESIN

PRODUCT #- 4100A

PRODUCT CLASS- EPOXY RESIN

HMIS CODE HEALTH-1 , FIRE-1, REACTIVITY-0

HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME

## SECTION II: HAZARDOUS INGREDIENTS      CAS      %      PEL      TLV

EPOXY RESIN                                      25068-38-6      limits have not been established

Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption.

## SECTION III: PHYSICAL DATA

BOILING RANGE: > 300F

EVAPORATION RATE VS BUTYL ACETATE -na

VAPOR DENSITY VS AIR: na

SOLUBILITY IN WATER: not soluble

APPEARANCE AND ODOR: clear viscous

PERCENT VOLATILE BY VOLUME: 0

WEIGHT PER GALLON: 9.6b/gal

## SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT ( F ): +400F

LEL: na

UEL: na

EXTINGUISHING MEDIA: water spray, dry chemical, foam or carbon dioxide

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide, carbon monoxide, aldehydes.

SPECIAL FIRE FIGHTING PROCEDURES: water spray to keep containers cool, and to protect persons attempting to stop leaks. Wear goggles and full protective clothing. Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter, especially if sprayed into containers of hot material.

## SECTION V: HEALTH HAZARD DATA - EFFECTS OF OVER EXPOSURE

INGESTION: practically non toxic

INHALATION: excessive inhalation of vapors can cause nasal and respiratory irritation

SKIN ABSORPTION: prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

SKIN CONTACT: above

EYE CONTACT: can cause irritation, redness, tearing, blurred vision.

EFFECTS OF CHRONIC OVER EXPOSURE: NA

MSDS SHEET C.D. PRODUCTS INC. #4100 PART A EPOXY PAGE 2

EMERGENCY FIRST AID PROCEDURES

EYE CONTACT: flush with water for 15 minutes and seek medical attention

SKIN CONTACT: wash immediately with soap and water, remove contaminated clothing and launder before reuse.

INGESTION: do not induce vomiting, keep person warm and quiet and seek medical attention

INHALATION: remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped administer artificial respiration. Keep person warm and quiet and seek medical attention.

SECTION VI: REACTIVITY DATA

STABILITY: stable

HAZARDOUS POLYMERIZATION: will not occur

CONDITIONS TO AVOIDS excessive heat, contact with strong bases

SECTION VII: SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: eliminate ignition sources, absorb with inert material, eg- sand, scoop up and put into disposal container. flush area with water, prevent washdowns from entering the sewers and water ways. Uncontrolled spills which exceed one gallon may be reportable to the National Response Center. For small spills the resin may be scooped up and then disposed of.

WASTE DISPOSAL METHOD: Incinerate in furnace or dispose of in accordance with applicable local, state, and federal regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY: use with adequate ventilation. NIOSH/MSA approved respirators

should be used where ventilation is not adequate. Niosh approved air-line respirators with auxiliary escape air tanks or self contained breathing apparatus should be used in confined spaces.

VENTILATION: local exhaust recommended when appropriate to control employee exposure.

PROTECTIVE GLOVES: Neoprene, nitrile rubber -should be worn

EYE PROTECTION: chemical splash goggles

OTHER PROTECTIVE EQUIPMENT: normal work clothing covering arms and legs

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: avoid skin contact, remove and launder contaminated clothing. Empty containers may contain residual flammable vapors so all hazard precautions should be observed.

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: NA

OTHER PRECAUTIONS: keep away from heat or open flames

SECTION XI: SARA TITLE III INFORMATION

Supplier is notified under SARA TITLE III SECTION 313 not required for this product. SARA SECTION 311 and 312 hazard classification for this product is listed below

Immediate ( acute ) health hazard

Delayed ( chronic) health hazard

**SECTION XII: RCRA INFORMATION**

Since this product is not sold as a waste, we have not listed it as a waste. Based on our knowledge of this product, its raw materials and processes employed during its manufacture, we believe it is unlikely that this product is a hazardous waste for federal RCRA purposes. We recommend that you carry out your own tests and evaluations prior to discarding any materials.

**SECTION XIII: CERCLA INFORMATION**

Under EPA-CERCLA releases to air, land or water which exceed the reportable quantity must be reported to the national response center (800-424-8802). This product contains no materials with reportable quantities.

**SECTION XIV: CALIFORNIA PROPOSITION 65 INFORMATION**

This product is not subject to California Proposition 65 notification.

**SECTION XV: TRANSPORTATION INFORMATION**

Dot shipping name: not applicable

Dot hazard class: not required

Dot label(s): none

Dot UN/NA number: not applicable

**SECTION XVI: OTHER INFORMATION**

This product complies with all TSCA inventory requirements.

**NOTE:** To the best of our knowledge, the information contained herein is accurate. However C.D. Products. Inc assumes no liability whatsoever for the accuracy or completeness of the information contained herein. The final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.