

# MATERIAL SAFETY DATA SHEET

C.D. PRODUCTS, INC.                      emergency telephone #  
918 N. Union St..                      (920)-739-8685  
Appleton, WI 54911                      ISSUE DATE- 10/6/99

## SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME- NUPRIME PART A

PRODUCT #-

PRODUCT CLASS- EPOXY RESIN SOLUTION

HMIS CODE HEALTH-1 , FIRE-2, REACTIVITY-0

HAZARD RATING: 0=LEAST, 1=SLIGHT, 2= MODERATE, 3=HIGH, 4= EXTREME

SECTION II: HAZARDOUS INGREDIENTS	CAS	%	PEL	TLV
EPOXY RESIN (EPICHLOROHYDRIN/BISPHENOL A)	NE	Significant	N/E	N/E
ETHELENE GLYCHOL MONOPROPYL ETHER	002807-30-9	Minor	N/E	(1)Skin
non hazardous components				
water	7732-18-5	Moderate		

% Listing: 0-10% Minor, 10-35% Moderate 35-60% Significant >60% Major      N/E = Not Established

(1) Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorbtion.

## SECTION III: PHYSICAL DATA

BOILING RANGE: > 280F

EVAPORATION RATE VS BUTYL ACETATE - slower

VAPOR DENSITY VS AIR: heavier

SOLUBILITY IN WATER: moderately soluble

APPEARANCE AND ODOR: clear thin liquid, strong solvent odor

PERCENT VOLATILE BY VOLUME: 57%-clear

WEIGHT PER GALLON: 8.2b/gal-clear

## SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT ( F ): >120F

LEL: <1.1%                                      UEL: na

EXTINGUISHING MEDIA: water spray, dry chemical, foam or carbon dioxide

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide, carbon monoxide,

SPECIAL FIRE FIGHTING PROCEDURES: water spray to keep containers cool, and to protect persons attempting to stop leaks. Wear self contained breathing apparatus with a full face piece operated in the positive pressure demand mode, goggles and full protective clothing. Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter, especially is sprayed into containers of hot, burning liquid.

UNUSUAL FIRE AND EXPLOSION HAZARDS: closed containers may explode due to build up of pressure from excessive heat. vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights or other ignition sources at locations distant from the material handling point. Never weld on or near drum. Liquids or residues may ignite explosively.

## SECTION V: HEALTH HAZARD DATA - EFFECTS OF OVER EXPOSURE

INGESTION: can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

INHALATION: excessive inhalation of vapors can cause nasal and respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness, and even death.

SKIN ABSORPTION: prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

SKIN CONTACT: above

EYE CONTACT: can cause severe irritation, redness, tearing, blurred vision.

MSDS SHEET C.D. PRODUCTS INC. NUPRIME PART A-- PAGE 2

EFFECTS OF CHRONIC OVER EXPOSURE: NA

#### EMERGENCY FIRST AID PROCEDURES

EYE CONTACT: flush with water for 15 minutes and seek medical attention

SKIN CONTACT: wash immediately with soap and water, remove contaminated clothing and launder before reuse.

INGESTION: do not induce vomiting, keep person warm and quiet and seek medical attention

INHALATION: remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped administer artificial respiration. Keep person warm and quiet and seek medical attention.

#### SECTION VI: REACTIVITY DATA

STABILITY: stable

HAZARDOUS POLYMERIZATION: may occur-if in contact with amines or strong oxydizing agents.

CONDITIONS TO AVOIDS excessive heat, strong bases

#### SECTION VII: SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: eliminate ignition sources, absorb with inert material, eg- sand, scoop up and put into disposal container. flush area with water, prevent washdowns from entering the sewers and water ways. Uncontrolled spills which exceed one gallon may be reportable to the National Response Center.

WASTE DISPOSAL METHOD: Incinerate in furnace or dispose of in accordance with applicable local, state, and federal regulations.

#### SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY: use with adequate ventilation. NIOSH/MSA approved respirators

should be used where ventilation is not adequate. Niosh approved air-line respirators with auxiliary escape air tanks or self contained breathing apparatus should be used in confined spaces.

VENTILATION: local exhaust recommended when appropriate to control employee exposure.

PROTECTIVE GLOVES: Neoprene, nitrile rubber -should be warn

EYE PROTECTION: chemical splash goggles

OTHER PROTECTIVE EQUIPMENT: normal work clothing covering arms and legs

#### SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: avoid skin contact, remove and launder contaminated clothing. Empty containers may contain residual flammable vapors so all hazard precautions should be observed.

NOTE: To the best of our knowledge, the information contained herein is accurate. However C.D. Products. Inc assumes no liability whatsoever for the accuracy or completeness of the information contained herein. The final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

## MATERIAL SAFETY DATA SHEET

C.D. PRODUCTS, INC.  
918 N. Union St..  
Appleton, WI 54911

emergency telephone #  
(920)-739-8685  
ISSUE DATE- 10/06/99

### SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME- NUPRIME PART B

PRODUCT #-

PRODUCT CLASS- HARDENER SOLUTION

HMS CODE HEALTH-1 , FIRE-1, REACTIVITY-0

HAZARD RATING: 0=LEAST, 1=SLIGHT, 2= MODERATE, 3=HIGH, 4= EXTREME

### SECTION II: HAZARDOUS INGREDIENTS

	CAS	%	PEL	TLV
Epoxy hardener - proprietary	njrtk 678290-00-2-5111-p res (1)	Moderate		
ETHELENE GLYCHOL MONOPROPYL ETHER	002807-30-9	Minor	NA	(2)Skin
non hazardous components				
water	7732-18-5	Moderate		

% Listing: 0-10% Minor, 10-35% Moderate 35-60% Significant >60% Major N/E = Not Established

(1) See effects of over exposure

(2) Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption.

### SECTION III: PHYSICAL DATA

BOILING RANGE: > 300F

EVAPORATION RATE VS BUTYL ACETATE - slower

VAPOR DENSITY VS AIR: heavier

SOLUBILITY IN WATER: soluble

APPEARANCE AND ODOR: clear liquid, slight solvent odor

PERCENT VOLATILE BY VOLUME: 57,

WEIGHT PER GALLON: 8.7b/gal

### SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT ( F ): >120F

LEL: <1.1%

UEL: na

EXTINGUISHING MEDIA: water spray, dry chemical, foam or carbon dioxide

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide, carbon monoxide,

SPECIAL FIRE FIGHTING PROCEDURES: water spray to keep containers cool, and to protect persons attempting to stop leaks. Wear self contained breathing apparatus with a full face piece operated in the positive pressure demand mode, goggles and full protective clothing. Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter, especially is sprayed into containers of hot, burning liquid.

UNUSUAL FIRE AND EXPLOSION HAZARDS: closed containers may explode due to build up of pressure from excessive heat.

### HAZARD DATA - EFFECTS OF OVER EXPOSURE

**INGESTION:** may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

## MSDS SHEET NUPRIME PART B HARDENER -- PAGE 2

### SECTION V: HEALTH

**INHALATION:** excessive inhalation of vapors may cause nasal and respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness, and even death.

**SKIN ABSORPTION:** prolonged or repeated contact may cause moderate irritation, defatting, dermatitis.

**SKIN CONTACT:** above

**EYE CONTACT:** may cause severe irritation, redness, tearing, blurred vision

**EFFECTS OF CHRONIC OVER EXPOSURE:** NA

### EMERGENCY FIRST AID PROCEDURES

**EYE CONTACT:** flush with water for 15 minutes alternately lifting lids until no sign of product remains then seek medical attention

**SKIN CONTACT:** wash immediately with soap and water, remove contaminated clothing and launder before reuse. If irritation persists seek medical attention..

**INGESTION:** do not induce vomiting, keep person warm and quiet, dilute with large quantities of milk or water and seek medical attention

**INHALATION:** remove to fresh air. If breathing is difficult administer oxygen. If breathing has stopped administer artificial respiration. Keep person warm and quiet and seek medical attention.

### SECTION VI: REACTIVITY DATA

**STABILITY:** stable

**HAZARDOUS POLYMERIZATION:** will not occur

**CONDITIONS TO AVOIDS** excessive heat

### SECTION VII: SPILL OR LEAK PROCEDURE

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** eliminate ignition sources, absorb with inert material, eg- sand, scoop up and put into disposal container. flush area with water, prevent washdowns from entering the sewers and water ways. Uncontrolled spills which exceed one gallon may be reportable to the National Response Center. For small spills, pick up spilled material with sorbent material an shovel and dispose of in accordance with all federal, state, and local regulations.

**WASTE DISPOSAL METHOD:** Incinerate in furnace or dispose of in accordance with applicable local, state, and federal regulations.

### SECTION VIII: SPECIAL PROTECTION INFORMATION

**RESPIRATORY:** use with adequate ventilation. NIOSH/MSA approved respirators

should be used where ventilation is not adequate. Niosh approved air-line respirators with auxiliary escape air tanks or self contained breathing apparatus should be used in confined spaces.

**VENTILATION:** local exhaust recommended when appropriate to control employee exposure.

**PROTECTIVE GLOVES:** Neoprene, nitrile rubber -should be warn

**EYE PROTECTION:** chemical splash goggles

**OTHER PROTECTIVE EQUIPMENT:** normal work clothing covering arms and legs

## **SECTION IX: SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** avoid skin contact, remove and launder contaminated clothing. Empty containers may contain residual flammable vapors so all hazard precautions should be observed.

**NOTE:** To the best of our knowledge, the information contained herein is accurate. However C.D. Products, Inc assumes no liability whatsoever for the accuracy or completeness of the information contained herein. The final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.