

SAFETY DATA SHEET

C.D. PRODUCTS INC
918 N UNION ST
APPLETON, WI 54911
920-739-8685

1.IDENTIFICATION

1013 PART A EPOXY SOLUTION

2.HAZARDS IDENTIFICAION

Classification of the substance or : **FLAMMABLE LIQUIDS - Category 3 mixture**

ACUTE TOXICITY:oral - Category 4

ACUTE TOXICITY:inhalation - Category 4

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

[blood system, stomach] - Category 1

SPECIFIC TARGET ORGAN TOXICITY (REPEATED

GHS label elements

Hazard pictograms



Signal word : **Danger**

Date of previous issue

Hazard statements

Precautionary statements

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H370 Causes damage to organs: (blood system, stomach) H372 Causes damage to organs through prolonged or repeated exposure: (skin, kidneys)

H411 toxic to aquatic life with long lasting effects

Precautionary statements

1) Prevention

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P321 Specific treatment
- P330 Rinse mouth.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.

General : Not applicable.

Prevention :

Wear protective gloves.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical, ventilating, lighting and all materialhandling equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use only outdoors or in a well-ventilated area.

Do not breathe vapor.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Response : Get medical attention if you feel unwell.

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or physician if you feel unwell.

IF SWALLOWED:

Call a POISON CENTER or physician if you feel unwell.

Rinse mouth.

IF ON SKIN (or hair):

Take off immediately all contaminated clothing.
Rinse skin with water or shower.

IF ON SKIN:

Wash with plenty of soap and water.
Rinse mouth
Take off contaminated clothing.
If skin irritation or rash occurs: Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists:
Get medical attention.

Collect spillage

Storage : Store locked up.
Store in a well-ventilated place.
Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result : None known. in classification

3.COMPOSITION INFORMATION ON INGREDIENTS

Substance/mixture : Mixture

| Ingredient name | % by weight | CAS number |
|---|-------------|------------|
| 4,4'-(1-methylethylidene)bisphenol polymer with(chloromethyl)oxirane | 30-50 | 25068-38-6 |
| Ethylene Glycol Monopropyl Ether | 30-50 | 2807-30-9 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting

Occupational exposure limits, if available, are listed in Section 8.

4.FIRST AID MEASURES

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.
Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes.
Get medical attention. If necessary, call a poison center or physician.
In the event of any complaints or symptoms, avoid further exposure.
Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first aid personnel : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media
: Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products
: Decomposition products may include the following materials: carbon oxides aldehydes acids other organic compounds

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fireexposed containers cool.

Special protective equipment for fire-fighters
: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders
: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and

place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Control parameters

Occupational exposure limits None.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Individual protection measures

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

| | | |
|---|---|---|
| Physical state | : | Liquid |
| Color | : | Light yellow |
| Odor | : | ethereal. |
| Odor threshold | : | Not available |
| pH | : | Not available |
| Melting point/ Freezing point | : | Not available |
| Boiling point | : | 150 °C (302.00 °F) |
| Flash point | : | Setaflash Closed Cup: 54 °C (129.20 °F) (ASTM D 3828) |
| Burning time | : | Not available |
| Burning rate | : | Not available |
| Evaporation rate | : | Not available |
| Flammability (solid, gas) | : | Not available |
| Lower and upper explosive (flammable) limits | : | Lower: 1.6 %(V) (Solvent) Upper: 13 %(V) (Solvent) |
| Vapor pressure | : | 0.2 kPa @ 20 °C (68.00 °F) |
| Vapor density | : | 1 [Air = 1] |
| Relative density | : | Not available |
| Density | : | 1,060 kg/m ³ |

| | | |
|--|---|--|
| Solubility | : | Not available |
| Solubility in water | : | Partial |
| Partition coefficient: noctanol/water | : | Not available |
| Auto-ignition temperature | : | 240 °C (464.00 °F) (Solvent) |
| Decomposition temperature | : | Not available |
| SADT | : | Not available |
| Viscosity | : | Dynamic: Not available Kinematic: Not available |

Other information No additional information.

10. STABILITY AND REACTIVITY

This material is stable under recommended storage conditions

Reactivity

: Stable under normal conditions.

Chemical stability

: The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid exposure - obtain special instructions before use.

Incompatible materials : Reactive or incompatible with the following materials: strong alkalis, aliphatic amines,

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards

Reacts with considerable heat release with some curing agents.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

[4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : LD50 > 1000 mg/kg Rat

* Dermal

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : LD50 > 20000

mg/kg Rabbit

* Inhalation

| Product/ingredient name | Result | Species | Dose | Exposure |
|----------------------------------|--|---------|-------------|----------|
| Ethylene Glycol Monopropyl Ether | | | | |
| | LD50 Oral | Rat | 3,089 mg/kg | - |
| | LD50 Oral | Rat | 3,090 mg/kg | - |
| | LD50 Oral | Rat | 3,089 mg/kg | - |
| Remarks - Inhalation: | F29 Behavioral - Analgesia J22 Lung, Thorax, or Respiration - Dyspnea M14 Kidney, Ureter, and Bladder - Hematuria | | | |
| | LD50 Dermal | Rabbit | 870 mg/kg | - |

Conclusion/Summary : Not available

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|----------------------------------|------------------------|------------|-------|----------|-------------|
| Ethylene Glycol Monopropyl Ether | Skin - Mild irritant | Rabbit | | 24 hrs | - |
| | Skin - Mild irritant | Guinea pig | | | - |
| | eyes - Severe irritant | Rabbit | | 24 hrs | - |
| | eyes - Severe irritant | Rabbit | | | - |

Conclusion/Summary

Skin : Not available

eyes : Not available

Respiratory : Not available

Sensitization

Conclusion/Summary

Skin : Not available

Respiratory : Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

Reproductive toxicity

Conclusion/Summary : Not available

Teratogenicity

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|----------------------------------|--------------------------|-------------------|---|
| Ethylene Glycol Monopropyl Ether | Category 3 Category 1 | | Respiratory tract irritation blood system stomach |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|--|------------|-------------------|---------------|
| Phenol, polymer with formaldehyde, glycidyl ether, polymers with glycidyl tolyl ether and triethylenetetramine | Category 1 | | skin |
| Ethylene Glycol Monopropyl Ether | Category 1 | | kidneys |

Aspiration hazard

Not available

Information on the likely routes of available exposure : Not

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : Harmful if inhaled.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : Harmful if swallowed. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or
irritation
watering
redness
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following: irritation redness
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Long term exposure

Potential immediate effects : Not available

Potential delayed effects : Not available

Potential chronic health effects

Conclusion/Summary : Not available

General : Causes damage to organs through prolonged or repeated exposure: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available

12 ECOLOGICAL INFORMATION

A. Ecotoxicity

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : LC50 = 1.41 mg/ℓ 96 hr *Oryzias latipes*

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : EC50 = 1.7 mg/ℓ 48 hr

○ **Algae**

- Not available

B. Persistence and degradability

○ **Persistence**

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : log Kow = 2.821 (Estimates)

○ **Degradability**

- Not available

C. Bioaccumulative potential

○ **Bioaccumulative potential**

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : BCF = 0.56 ~ 0.67 (Exposure concentrations: 10ug/l, 5.6<=BCF<=6.8(Exposure concentrations: 1ug/l))

○ **Biodegradation**

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : Biodegradability = 0 (%) 28 day

D. Mobility in soil

- Not available

| Product/ingredient name | LogPow | BCF | Potential |
|----------------------------------|--------|-----|-----------|
| Ethylene Glycol Monopropyl Ether | 0.08 | - | low |

Mobility in soil

Soil/water partition coefficient (KOC) : Not available
Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORTATION CONSIDERATIONS

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

| Regulatory information | UN/NA number | Proper shipping name | Classes/*PG | Reportable Quantity (RQ) |
|------------------------|--------------|---------------------------|-------------|--------------------------|
| CFR | 1866 | RESIN SOLUTION, flammable | Class 3 III | |

| | | | |
|---------------------|------|---------------------------|-------------|
| TDG | 1866 | RESIN SOLUTION, flammable | Class 3 III |
| IMO/IMDG | 1866 | RESIN SOLUTION, flammable | Class 3 III |
| IATA (Cargo) | 1866 | RESIN SOLUTION, flammable | Class 3 III |

*PG : Packing group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.'

15 .REGULATORY INFORMATION

United States

o Information of EU Classification NA

* Classification

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : Xi; R36/38 R43 N; R51-53

* Risk Phrases

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : R36/38, R43, R51/53

* Safety Phrase

- [4,4'-(1-methylethylidene)bisphenol polymer with (chloromethyl)oxirane] : S2, S28, S37/39, S61

U.S. Federal regulations : **United States - TSCA 12(b) - Chemical export notification:** None required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed **United States - TSCA 5(a)2 - Proposed significant new use rules:** Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

SARA 313

| | | Product name | CAS number |
|--|---|---------------------|-------------------|
| Form R - Reporting requirements | : | Ethanol, 2-propoxy- | 2807-30-9 |

| | | | |
|-----------------------|---|---------------------|-----------|
| Supplier notification | : | Ethanol, 2-propoxy- | 2807-30-9 |
|-----------------------|---|---------------------|-----------|

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

California Prop. 65: : None required.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
Class D-1B: Material causing immediate and serious toxic effects (Toxic). Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : None required.

CEPA Toxic substances : None required.

International regulations

International lists :

- Australia inventory (AICS):** All components are listed or exempted.
- Canada inventory:** At least one component is not listed in DSL but all such components are listed in NDSL.
- Japan inventory:** All components are listed or exempted.
- China inventory (IECSC):** All components are listed or exempted.
- Korea inventory:** All components are listed or exempted.
- New Zealand Inventory (NZIoC):** All components are listed or exempted.
- Philippines inventory (PICCS):** Not determined.
- United States inventory (TSCA 8b):** All components are listed or exempted.
- Taiwan inventory (CSNN):** All components are listed or exempted.

16. OTHER INFORMATION

Hazardous Material Information System III (U.S.A.) :

| | | |
|--------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |

| | |
|-------------------------|---|
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Date of printing : 11/11/15

Date of issue/Date of revision : 11/11/15

Date of previous issue : 01/15/1999

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

UN = United Nations

References : Not available

Notice to reader

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.