



PRODUCTS, INC.

918 N. UNION STREET
APPLETON, WI 54911
920-739-8685
OR 1-800-221-6381

**EPOXY & FIBERGLASS FLOORING, SEAMLESS FIBERGLASS WALL SYSTEMS, SEALERS,
HIGH PERFORMANCE COATING SYSTEMS, AND INDUSTRIAL CLEANERS**

PRODUCT BULLETIN **OIL STOP EPOXY PRIMER**

DESCRIPTION: OIL STOP EPOXY PRIMER is specifically designed as a long term barrier coating for oil or grease soaked concrete floors. Part B is slightly tan/white and **Part A is dark brown/black**. The mixed materials is a very thin brown liquid that should be applied evenly. After as thorough a clean as possible, OIL STOP PRIMER will adhere to the formerly contaminated floor and provide a barrier for any oil soaked into the concrete from migrating up and delaminating the subsequent topping system.

USES: typical uses are machine shops, truck and auto repair shops, oil and lube centers and other areas where frequent oil spills have occurred over time soaking the concrete with oil.

APPLICATION: Proper surface preparation is essential. Thoroughly clean with CD-103 using heavy mechanical scrubbing and or hot pressure washing. Rinse thoroughly and repeat as necessary to get the surface clean. **DO NOT SHOT BLAST** as this will drive the oil deeper into the concrete and likely cause delamination problems later. Mix parts A And B in equal proportions and apply at 250-300 sqft per gallon evenly over the surface. Allow to cure (over night is recommended) and then continue on with the application of the subsequent surface. Do not apply when temperatures are below 60F or above 90F. Use as is. No thinning for spraying is required.

SPECIFICATIONS

POT LIFE 2-4 HR

TACK FREE 2-4 HR

RECOAT 4- 8 HR

LIGHT FOOT TRAFFIC 16-24 HR

FULL CURE 3-7 DAYS

COLOR BLACK ONLY

CHEMICAL RESISTANCE- THIS IS CONSIDERED A PRIMER FOR MORE RESISTANT COATINGS

MOST SOLVENTS – GOOD

MOST ALKALAI S – SPLASH ONLY

MOST ACIDS- SPLASH ONLY

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER C.D. PRODUCTS INC. ASSUMES NO LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. THE FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSE OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTY THAT THESE ARE THE ONLY HAZARDS WHICH EXIST.

2X5 GAL \$190.00/GAL